


Indoor distribution box installation distance requirements

Overview

Clearance: Electrical panels must be installed in a readily accessible area with a minimum clearance of 30 inches (762 mm) wide, 3 ft (36 inches or 914 mm) deep, and 6.5 feet ($\approx$ 2 meter) high in front of the panel. The panelboard's door (hinged cover) shall be able to be opened to a. Choose the right box based on environment (indoor/outdoor), load capacity, and durability. Check for proper IP/NEMA ratings and material quality. Exposed live parts on one side of the working space and no live or grounded parts (including concrete, brick, or tile walls) on the other side of the working space. Concrete, brick, tile, and similar. These requirements vary depending on whether the electrical equipment is rated at (1) 1,000 volts or less (See, Article #2) or (2) over 1,000 volts. Minimum clearances in front of electrical equipment (600 V (now 10000 V) or. This paper will review some of the NEC requirements regarding required electrical space and discuss new product concepts serving to reduce equipment size, resulting in reduced space requirements, reduced installation time, and reduced installation costs.



Article Content

Jul 21, 2026

Working Clearances, based on the 2020 NEC

For indoor installations, the footprint space (width and depth of the equipment) extending from the floor to a height of 6 ft above the equipment or to the structural ceiling, whichever is lower, must be ...

Jun 06, 2026

1910.303

The work space shall be clear and extend from the grade, floor, or platform to the height required by paragraph (g) (1) (vi) of this section. However, other equipment associated with the electrical ...

Jul 05, 2026

UFC 3-520-01 Interior Electrical Systems

Arrange circuits throughout the distribution system with 5% or less design load imbalance for both single- and three-phase systems. Show load imbalance by phase as a percentage on the panel, ...

Aug 30, 2025

Electrical equipment floor space

This paper will review some of the NEC requirements regarding required electrical space and discuss new product concepts serving to reduce equipment size, resulting in reduced space requirements, ...

Nov 29, 2025

NEC Article 110.34: Electrical Room "Basics"

Minimum clearances are established for work spaces in front of high voltage - electrical equipment such as switchboards, control panels, switches, circuit breakers, switchgear and motor controllers. These ...

Oct 24, 2025

110.26 (E) Dedicated Equipment Space.

This dedicated space is dedicated specifically to the electrical installation. No piping, ductwork, leak protection systems, or other equipment that is foreign to the electrical installation is permitted in this ...

Oct 07, 2025

The installation requirements for the distribution box

Learn how to install a distribution box safely and correctly. Covers wiring, placement, standards, and expert tips for a compliant setup.

Nov 11, 2025

Service Disconnect Rules per NEC Article 230, Part VI

A detailed look at NEC Article 230, Part VI, covering the requirements for service disconnecting means, including location, rating, and grouping.

Apr 11, 2026

NEC Requirements for Panelboards and Load Centers

Clearance: Electrical panels must be installed in a readily accessible area with a minimum clearance of 30 inches (762 mm) wide, 3 ft (36 inches or 914 mm) deep, and 6.5 feet ($\approx$ 2 meter) high in front of ...

Nov 18, 2025

Electrical Clearances: Requirements and Safe Distances

Every electrical panel, breaker box, meter base, and service disconnect needs a clear working zone in front of it so that someone can safely operate the equipment or respond to an ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.iiss.co.za>

Email: sales@iiss.co.za

Phone: +27 63 174 2895

Address: Unit 8, Innovation Park, 15 Rivonia Road, Sandton, Johannesburg, 2196, South Africa

This document is for informational purposes only. Specifications subject to change without notice.

