

Width of Serbian Aluminum Alloy Cable Trays

Overview

Size : 50mm to 900mm in width and 25mm to 150mm in height. All tray sections will support an additional 200 lb concentrated load on any portion of tray (side rail, rung, etc.) above and beyond published load class. Extra wide. Cable trays - Cable trays, screw connection. 56A NOMINAL ALUMINUM LADDER TYPE CABLE TRAY 6" NOMINAL OUTSIDE DEPTH RUNG 5" NEMA LOADING DEPTH SPACING 1" CABLE ALUMINUM ALLOY 6063-T6, COPPER FREE MARINE GRADE BEARING UL CROSS SECTIONAL AREA: 2. SURFACE CLASSIFIED BY UNDERWRITERS LABORATORIES, INC. 12 18 360 *TO DETERMINE DEFLECTION. In practice, cable tray dimensions are a system of interrelated measurements —width, depth, length, and material thickness—that directly affect cable fill compliance, heat dissipation, structural loading, and long-term expandability. All calculations and data are based on 36" wide cable trays with rungs spaced on 12" centers with tray supported as simple spans with deflection measured at the midpoint.



Article Content

Nov 03, 2025

Cable Tray Width, Dimensions and Specifications as per ...

Learn about cable tray width dimensions and specifications as per NEC standards. Understand types, sizes, materials, and installation guidelines for safe and ...

Jan 17, 2026

Cable Tray Dimensions Guide: Standard Sizes, Tray Types & Sizing ...

Explore standard sizes by tray type, understand width and depth limits, and see how to calculate and choose compliant cable tray sizes for real projects.

Mar 23, 2026

CABLE TRAY CABLE TRAY

Size: ous sizes. Length starting from 2000 up to 6000 mm. Width starting from 100 up to 900 mm. Flange Height starting from 25 up *Other sizes are available upon request.

Dec 08, 2025

12-SDMS-06

Cable tray supports shall have a maximum of 6 m spacing on horizontal run and 2.4 m spacing on the vertical runs. However, when the tray system is supported from building structure with rods, brackets ...

Jan 04, 2026

Aluminum Cable Ladder Specifications | PDF | Screw

The document discusses aluminum cable ladder products from series 2, 3, 4, and 5. It provides information on straight sections, accessories, fittings, and fitting covers.

Oct 13, 2025

Cable Management System

WESTRAYS are supplied in 2.44 meter or 3.0 meter or 3.66 meter standard lengths. The channel type trays are manufactured in various widths & heights of aluminum or hot dipped galvanized carbon ...

Oct 23, 2025

Cable Tray Dimensions Guide: Standard Sizes, Tray ...

Explore standard sizes by tray type, understand width and depth limits, and see how to calculate and choose compliant cable tray sizes for real projects.

Sep 07, 2025

CableTray Book English

All calculations and data are based on 42 in. wide cable trays with rungs spaced on 12 in. centers with tray supported as simple spans with deflection measured at the midpoint. Continuous spans may ...

Aug 01, 2025

88615_Aluminum01-51

All calculations and data are based on 36" wide cable trays with rungs spaced on 12" centers with tray supported as simple spans with deflection measured at the midpoint.

Mar 09, 2026

Cope Ladder Master Spec

Aluminum Tray - Splice plates shall be made of 6063-T6 aluminum, using ribbed neck spline bolts and serrated flange locknuts. Hardware shall be zinc plated in accordance with ASTM B633, SC1.

May 31, 2026

S00004107-56a-aluminum-straight-section-56-standard-rung ...

*TO DETERMINE DEFLECTION, MULTIPLY THE ANTICIPATED LOAD (lbs/ft or kg/m) BY THE DEFLECTION MULTIPLIER. RESULTS WILL BE IN INCHES OR MILLIMETERS.

Sep 06, 2025

TECHNICAL AND SIZING DATA

Even though a 900 mm wide tray has six (6) times the volume of a 150 mm wide tray, it cannot carry any more cable weight. When piling cable in tray, the required air separation between cables can be ...

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.iiss.co.za>

Email: sales@iiss.co.za

Phone: +27 63 174 2895

Address: Unit 8, Innovation Park, 15 Rivonia Road, Sandton, Johannesburg,
2196, South Africa

This document is for informational purposes only. Specifications subject to
change without notice.

